

1-1004: U2W Poli-Glide Standard

Color: White

Plies: 2

Nom. OAG: 0.06" +/- 0.015"

Fabric: Monofilament

Top Surface: Smooth Cover

Bottom Surface: Bare

Weight: 0.023 lbs./PIW

Compound: Poly Urethane Work Tension: 50 lbs./PIW Elongation: Less than 1%

Minimum Pulley: 0.1"

Backflex Min. Pulley Dia.: 0.2" **Working Temp. (F):** -4 to 180

Max. Stocked Width: 72"

Attributes: Cross Rigid, Abrasion

Resistant, FDA Compliant, Oil Resistant,

Sliderbed Suitable

Hardness: 90a

Features: This belt is a lightweight 2 ply monofilament construction that will negotiate small pulleys. The urethane compound is oil, animal fat and grease resistant. It is easy to clean and will lay flat. Refer to the chemical resistance chart when choosing a cleaning solution. This belt is formulated for use in metal detectors and is not anti-static. U2W Poli-Glide Standard is used in candy, chocolate and confectionery processing. It is also used in many medium food processing applications such as the cheese, bakery, fish, meat, poultry and vegetable industries. It is also metal detector compliant.






Ph: (800) 253-6300

Fax: (201) 337-6540

sales@mulhernbelting.com www.mulhernbelting.com

Splicing Instructions

Part Number: 1-1004 Part Description: U2W Poli-Glide Standard



Finger Length (A):

Finger Width (B):

Imperial	Metric	
12"	305 mm	
7"	178 mm	

Water Cooled

Hi-Speed

Upper Platen Temp:

Bottom Platen Temp:

Pressure:

Time:

Imperial	Metric	Imperial	Metric
100 ° F	38 ° C	120 ° F	49 ° C
200 ° F	93 ° C	210 ° F	99 ° C
500 PSI	34.5 bar	300 PSI	20.7 bar
10:00 m:s	10:00 m:s	15:00 m:s	15:00 m:s

Press Layout Description Top Heating Platen with equalizing plate Silicone Paper White Urethane Foil Belt Silicone Paper Molleton Cloth Bottom Heating Platen with equalizing plate