



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-1005: U2W Poli-Glide 5M/2U/BU-A/S

Color: White

Plies: 2

Nom. OAG: 0.06" +/- 0.015"

Fabric: Monofilament

Top Surface: Smooth Cover

Bottom Surface: Bare

Compound: Poly Urethane

Work Tension: 50 lbs./PIW

Elongation: Less than 1%

Weight: 0.03 lbs./PIW

Minimum Pulley: 0.1"

Backflex Min. Pulley Dia.: 0.2"

Working Temp. (F): -4 to 180

Max. Stocked Width: 78.75"

Attributes: Abrasion Resistant, Anti-Static, Cross Rigid, FDA Compliant, Nosebar Suitable, Oil Resistant

Hardness: 90a

Features: This belt is a lightweight 2 ply monofilament construction that will negotiate small pulleys. The urethane compound is oil, animal fat and grease resistant. It is easy to clean and will lay flat. Refer to the chemical resistance chart when choosing a cleaning solution. This belt is anti-static. U2W Poli-Glide A/S is used in candy, chocolate and confectionery processing. It is also used in many medium food processing applications such as the cheese, bakery, fish, meat, poultry and vegetable industries.



Part #:

Part Description.:

| | Imperial | Metric |
|----------------|---------------------------------|-------------------------------------|
| Finger Length: | <input type="text" value="20"/> | <input type="text" value="508.00"/> |
| Finger Width: | | |

Water Cooled

| | Imperial | Metric |
|---------------------|----------|--------|
| Upper Platen Temp: | | |
| Bottom Platen Temp: | | |
| Pressure: | | |
| Time: | | |

Hi-Speed

| | Imperial | Metric |
|---------------------|----------|--------|
| Upper Platen Temp: | | |
| Bottom Platen Temp: | | |
| Pressure: | | |
| Time: | | |