



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 1-2006: 3 Ply OHGR - HD

**Color:** White

**Plies:** 3

**Nom. OAG:** 0.156" +/- 0.02"

**Fabric:** Polyester

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.046"

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.09 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** FDA Compliant, Oil Resistant,  
Sliderbed Suitable

**Top Cover Coefficient of Friction:** 1.8

**Bottom Cover Coefficient of Friction:**  
0.4

**Features:** 1-2006 features a special fabric treatment to ensure the highest ply adhesion with the lowest moisture retention. Please refer to the chemical resistance chart before choosing a cleaning solution. 3 Ply OHGR-HD is the heavy duty version of our popular 1-2003. It is used in most all FDA and agricultural applications due to its low moisture absorption and high oil resistance. This belt is very popular in the meat and fish industry.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39