



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-3004: 4 Ply White Nitrile/OHGR

Color: White

Plies: 4

Nom. OAG: 0.158" +/- 0.02"

Fabric: Cotton/Polyester

Top Surface: 3/64" Smooth Cover

Bottom Surface: Friction Surface

Compound: NBR

Work Tension: 140 lbs./PIW

Elongation: Less than 2%

Weight: 0.085 lbs./PIW

Minimum Pulley: 3"

Backflex Min. Pulley Dia.: 4.5"

Working Temp. (F): 0 to 250

Max. Stocked Width: 72"

Attributes: FDA Compliant, Oil Resistant,
Sliderbed Suitable

Top Cover Coefficient of Friction: 1.4

Bottom Cover Coefficient of Friction:
0.3

Features: 1-3004 features a special fabric treatment to insure the highest ply adhesion and the lowest moisture absorption. Refer to the Chemical Resistance Chart when choosing a cleaning solution. 4 Ply Nitrile can be used in any heavy duty food application. This belt has low moisture absorption and high resistance to oil and grease. This belt is very popular in the meat and fish industry.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39