



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 1-3007: 3 Ply White FS x FS

**Color:** White

**Plies:** 3

**Nom. OAG:** 0.09" +/- 0.01"

**Fabric:** Cotton/Polyester

**Top Surface:** Friction Surface

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 48 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.055 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** FDA Compliant, Oil Resistant

**Top Cover Coefficient of Friction:** 0.3

**Bottom Cover Coefficient of Friction:**  
0.3

**Features:** This belt features 3 plies of 15 oz. Cotton/Polyester fabric. The belt is flexible and easy to clean. Refer to the chemical resistance chart before choosing a cleaning solution. 3 Ply FS x FS has been used for many years as a general purpose bakery belt. It is commonly used on dough sheeters.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39