



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 1-4002: 2 Ply Tylerwire

**Color:** White

**Plies:** 2

**Nom. OAG:** 0.115" +/- 0.015"

**Fabric:** Polyester/Nylon

**Top Surface:** Tylerwire Impression

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 100 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.056 lbs./PIW

**Minimum Pulley:** 2"

**Backflex Min. Pulley Dia.:** 3"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** FDA Compliant, Oil Resistant,  
Sliderbed Suitable

**Top Cover Coefficient of Friction:** 1.3

**Bottom Cover Coefficient of Friction:**  
0.3

**Features:** This belt features a molder top surface that is excellent for moderate inclines and for dough forming. The belt is easy to clean, flexible and non-marking. Refer to the chemical resistance chart when choosing a cleaning solution. 2 Ply Tylerwire is used for dough forming, inclines, pulley lagging and laundry machines.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39