



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-4002Z: Tylerwire Zip-Link

Color: White

Plies: 1

Nom. OAG: 0.165" +/- 0.02"

Fabric: Plastic Mesh

Top Surface: Tylerwire Impression

Bottom Surface: Skim

Compound: NBR

Work Tension: 150 lbs./PIW

Elongation: Less than 2%

Weight: 0.07 lbs./PIW

Minimum Pulley: 3"

Backflex Min. Pulley Dia.: 4.5"

Working Temp. (F): 0 to 250

Max. Stocked Width: 72"

Attributes: FDA Compliant, Oil Resistant

Top Cover Coefficient of Friction: 1.3

Bottom Cover Coefficient of Friction:
0.4

Features: 1-4002Z features a ziplink splice to solve problems in applications where lace retention or installing an endless belt is a problem. Tylerwire Ziplink is a problem solving belt for light and medium industrial applications. The Ziplink splice is smooth and non-metallic and combines the convenience of a laced belt with the splice tension rating of an endless belt. This belt is used in bakery applications and anywhere a belt with a slight impression is needed.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39