



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-4003: 3 Ply Tylerwire

Color: White

Plies: 3

Nom. OAG: 0.155" +/- 0.015"

Fabric: Polyester

Top Surface: Tylerwire Impression

Bottom Surface: Friction Surface

Compound: NBR

Work Tension: 150 lbs./PIW

Elongation: Less than 2%

Weight: 0.074 lbs./PIW

Minimum Pulley: 2.5"

Backflex Min. Pulley Dia.: 3.75"

Working Temp. (F): 0 to 250

Max. Stocked Width: 72"

Attributes: FDA Compliant, Oil Resistant,
Sliderbed Suitable

Top Cover Coefficient of Friction: 1.3

Bottom Cover Coefficient of Friction:
0.3

Features: This belt features a molded top surface that is excellent for moderate inclines and dough forming. The belt is easy to clean, flexible and non-marking. Refer to the chemical resistance chart when choosing a cleaning solution. 3 Ply Tylerwire is used for dough forming, inclines, pulley lagging and in the laundry industry.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39