



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 1-4006: 3 Ply Pyramid Top

**Color:** White

**Plies:** 3

**Nom. OAG:** 0.204" +/- 0.02"

**Fabric:** Polyester

**Top Surface:** Pyramid Profile

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 90 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.1 lbs./PIW

**Minimum Pulley:** 2.5"

**Backflex Min. Pulley Dia.:** 3.75"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 60"

**Attributes:** FDA Compliant, Oil Resistant,  
Sliderbed Suitable

**Top Cover Coefficient of Friction:** 1.3

**Bottom Cover Coefficient of Friction:**  
0.5

**Features:** This belt features a high pyramid style profile that is molded on a stable polyester carcass. Refer to the chemical resistance chart before choosing a cleaning solution. NOTE--The profile must be recessed to use lacing. 3 Ply Pyramid Top is popular in many bakery applications requiring an FDA approved profile. This belt is also popular as pulley lagging.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39