



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-5001: 3 Ply Meat Cleat

Color: White

Plies: 3

Nom. OAG: 0.255" +/- 0.02"

Recessed OAG: 0.17"

Fabric: Polyester

Top Surface: Meat Cleat Impression

Bottom Surface: Friction Surface

Compound: NBR

Work Tension: 150 lbs./PIW

Elongation: Less than 2%

Weight: 0.1 lbs./PIW

Minimum Pulley: 2"

Backflex Min. Pulley Dia.: 3.5"

Working Temp. (F): 0 to 250

Max. Stocked Width: 72"

Attributes: FDA Compliant, Oil Resistant,
Sliderbed Suitable

Top Cover Coefficient of Friction: 1

Bottom Cover Coefficient of Friction:
0.3

Features: 1-5001 features a special fabric treatment to insure the highest ply adhesion possible combined with the lowest moisture retention. Refer to the chemical resistance chart before choosing a cleaning solution. 3 Ply Meat Cleat is popular in the meat and chicken industry to convey raw meat or chicken up inclines. It is highly resistant to oil, grease and cleaning solvents.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39