



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 1-5002: 2 Ply Teflon

**Color:** White

**Plies:** 2

**Nom. OAG:** 0.065" +/- 0.015"

**Fabric:** Polyester

**Top Surface:** Teflon Cover

**Bottom Surface:** Friction Surface

**Compound:** PTFE (Teflon)

**Work Tension:** 60 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.037 lbs./PIW

**Minimum Pulley:** 1.5"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 60"

**Attributes:** FDA Compliant, Sliderbed  
Suitable

**Top Cover Coefficient of Friction:** 0.25

**Bottom Cover Coefficient of Friction:**  
0.3

**Features:** 1-5002 features a teflon cover that is bonded to a high strength polyester carcass. The belt offers superb release qualities demanded by applications where hot or sticky materials are encountered. 2 Ply Teflon is popular in the confectionary, baking and other food processing industries. The teflon top cover offers excellent release qualities.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39