



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-5003: 3 Ply Teflon

Color: White

Plies: 3

Nom. OAG: 0.08" +/- 0.015"

Fabric: Polyester

Top Surface: .002 Thick Teflon

Bottom Surface: Friction Surface

Compound: PTFE (Teflon)

Work Tension: 100 lbs./PIW

Elongation: Less than 2%

Weight: 0.043 lbs./PIW

Minimum Pulley: 2"

Working Temp. (F): 0 to 250

Max. Stocked Width: 60"

Attributes: FDA Compliant, Sliderbed Suitable

Top Cover Coefficient of Friction: 0.25

Bottom Cover Coefficient of Friction: 0.3

Features: This belt features a .002" thick teflon cover that is bonded to a high strength polyester carcass. The belt offers superb release qualities demanded by applications where hot or stick materials are encountered. Refer to the chemical resistance chart when choosing a cleaning solution. This belt is not recommended for troughing or back bend applications. 3 Ply Teflon is popular in confectionary, bakery and other food processing applications.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39