



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-5005: 3 Ply Butyl

Color: White

Plies: 3

Nom. OAG: 0.103" +/- 0.01"

Fabric: Polyester

Top Surface: Matte

Bottom Surface: Friction Surface

Compound: Butyl

Work Tension: 105 lbs./PIW

Elongation: Less than 2%

Weight: 0.07 lbs./PIW

Minimum Pulley: 2.5"

Backflex Min. Pulley Dia.: 3.75"

Working Temp. (F): -65 to 300

Max. Stocked Width: 72"

Attributes: FDA Compliant, Heat Resistant, Sliderbed Suitable

Top Cover Coefficient of Friction: 1.2

Bottom Cover Coefficient of Friction: 0.4

Features: This belt features a butyl cover and butyl skims which give the belt a temperature range of -65F to a high of 300F. Please consult the Chemical Resistance Chart before choosing a cleaning solution. 3 Ply Butyl is designed for applications where temperature extremes are encountered such as freezing or frying operations. Please note the belt will shrink 1% is used over 275F.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39