



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-6003: 3 Ply Neoprene FS x FS

Color: Brown

Plies: 3

Nom. OAG: 0.066" +/- 0.01"

Fabric: Cotton/Polyester

Top Surface: Friction Surface

Bottom Surface: Friction Surface

Compound: NBR

Work Tension: 33 lbs./PIW

Elongation: Less than 2%

Weight: 0.037 lbs./PIW

Minimum Pulley: 1"

Backflex Min. Pulley Dia.: 1.5"

Working Temp. (F): 0 to 250

Max. Stocked Width: 72"

Attributes: Non-Marking

Top Cover Coefficient of Friction: 0.5

Bottom Cover Coefficient of Friction:
0.5

Features: 3 Ply Neoprene FS x FS features tightly woven fabric for general conveying. The belt is non-marking, very flexible, oil resistant and easy to clean. This belt can be made endless with cold vulcanizing cement as well as hot vulcanizing. Used to convey light duty products in most general industrial applications. Very popular in the printing industry.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39