



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-6009: 9 Ply Neoprene FS x FS

Color: Brown

Plies: 9

Nom. OAG: 0.22" +/- 0.02"

Fabric: Cotton/Polyester

Top Surface: Friction Surface

Bottom Surface: Friction Surface

Compound: NBR

Work Tension: 90 lbs./PIW

Elongation: Less than 2%

Weight: 0.118 lbs./PIW

Minimum Pulley: 4"

Backflex Min. Pulley Dia.: 6"

Working Temp. (F): 0 to 250

Max. Stocked Width: 72"

Attributes: Non-Marking

Top Cover Coefficient of Friction: 0.5

Bottom Cover Coefficient of Friction:
0.5

Features: This belt features tightly woven fabric for general conveying. The belt is non-marking, very flexible, oil resistant and easy to clean. This belt can be made endless with cold vulcanizing cement as well as hot vulcanizing. 9 Ply Neoprene FS x FS is used to convey medium weight parts, particularly in oily applications. It is very popular in the folding carton and printing industries.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39