



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-7004: U2W Poli-Dual 6S/FU/BU

Color: White

Plies: 2

Nom. OAG: 0.06" +/- 0.015"

Fabric: Cotton/Polyester

Top Surface: Bare

Bottom Surface: Bare

Compound: Poly Urethane

Work Tension: 80 lbs./PIW

Elongation: Less than 2%

Weight: 0.03 lbs./PIW

Minimum Pulley: 0.16"

Backflex Min. Pulley Dia.: 0.25"

Working Temp. (F): 0 to 180

Max. Stocked Width: 72"

Attributes: FDA Compliant, Oil Resistant

Features: 1-7004 features a cotton polyester blend for a multitude of bakery applications that previously used cotton. The fabric, combined with a urethane skim, yields low stretch and strong, smooth splices that can navigate nose bar pulleys. It simulates cotton belts in that it will release wet dough. U2W Poli-Dual 6S/FU/BU is used in most bakery applications requiring bare surface belts; rotary molding applications, pretzel proofing, wet dough conveying, cutting aprons and divider-rounder belts.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39