



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-7005: R2W Poli-Glide 8M/BR/BR

Color: White

Plies: 2

Nom. OAG: 0.065" +/- 0.01"

Fabric: Polyester

Top Surface: Urethane Impregnation

Bottom Surface: Urethane Impregnation

Compound: PVC

Work Tension: 50 lbs./PIW

Elongation: Less than 2%

Weight: 0.032 lbs./PIW

Minimum Pulley: 1"

Backflex Min. Pulley Dia.: 1.5"

Working Temp. (F): 20 to 180

Max. Stocked Width: 78.75"

Attributes: FDA Compliant

Features: The bare x bare polyester construction offers low friction on both sides of this belt. The belt is laterally stable and flexible. It is ideal for accumulating and picking belts with or without diverters. Refer to the chemical resistance chart before choosing a cleaning solution. R2W Poli-Glide 8M/BR/BR is in bakery applications, automated packaging machines, canning machines, paper and cardboard converting and as a proofing belt.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39