



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

1-7010: U2W Poli-Urethane

Color: White

Plies: 2

Nom. OAG: 0.06" +/- 0.015"

Fabric: Polyester

Top Surface: Friction Surface

Bottom Surface: Friction Surface

Compound: Poly Urethane

Work Tension: 45 lbs./PIW

Elongation: Less than 2%

Weight: 0.03 lbs./PIW

Minimum Pulley: 0.6"

Backflex Min. Pulley Dia.: 1"

Working Temp. (F): -22 to 176

Max. Stocked Width: 48"

Attributes: FDA Compliant, Nosebar
Suitable, Oil Resistant

Features: This is a two ply spun polyester with a urethane skim between the plies. The top and bottom surface is treated with urethane for extra life. The belt will handle the smallest pulleys. Refer to the chemical resistance chart when choosing a cleaning solution. U2W Poli-Glide 5M/FP/FP is one of the most widely used bakery belts today. The surface on the top and bottom prevents the conveyed product from sticking. It is an excellent belt for raw or cooked dough, baked goods, vegetables and cookies. Do not use with chocolate.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39