



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

2-1200: B2000 FBS

Color: Black

Plies: 1

Nom. OAG: 0.185" +/- 0.02"

Fabric: Interwoven Polyester

Top Surface: Friction Surface

Bottom Surface: Friction Surface

Compound: PVC

Work Tension: 200 lbs./PIW

Elongation: Less than 2%

Weight: 0.095 lbs./PIW

Minimum Pulley: 4"

Backflex Min. Pulley Dia.: 6"

Working Temp. (F): 0 to 180

Max. Stocked Width: 72"

Attributes: Fire Retardant, Sliderbed
Suitable

Top Cover Coefficient of Friction: 0.25

Bottom Cover Coefficient of Friction:
0.23

Features: 2-1200 features a tough carcass that is ideal for oily and abrasive areas and stamping plants. The belt is very stable and stays in place when diverted or sorted upon. B2000 FBS is used in heavy duty applications such as stamping plants as well as package sorting and diverting.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39



Splicing Instructions

Part Number: 2-1200

Part Description: B2000 FBS



Finger Length (A):

Finger Width (B):

Imperial	Metric
3"	76 mm
3/4"	19 mm

Water Cooled

Hi-Speed

Upper Platen Temp:

Bottom Platen Temp:

Pressure:

Time:

	Imperial	Metric	Imperial	Metric
Upper Platen Temp:	340 ° F	171 ° C	340 ° F	171 ° C
Bottom Platen Temp:	340 ° F	171 ° C	340 ° F	171 ° C
Pressure:	50 PSI	3.4 bar	36 PSI	2.5 bar
Time:	01:00 m:s	01:00 m:s	03:00 m:s	03:00 m:s

Press Layout

Description

Part # to Order

	Top Heating Platen with equalizing plate	
	Teflon	6-3000
	Meltable Foil (optional)	8341C
	Belt	2-1200
	Teflon	6-3000
	Bottom Heating Platen with equalizing plate	

For high stress applications splice with reinforcing fabric.