



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 2-1222: PC2 B225 CBS

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.28" +/- 0.02"

**Fabric:** Interwoven Polyester

**Top Surface:** Smooth Cover

**Bottom Surface:** Smooth Satin

**Compound:** PVC

**Work Tension:** 220 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.16 lbs./PIW

**Minimum Pulley:** 5"

**Backflex Min. Pulley Dia.:** 7.5"

**Working Temp. (F):** -20 to 180

**Max. Stocked Width:** 72"

**Attributes:** Cross Rigid, Static

Conductive to  $< 3 \times 10^8$  ohms, OSHA 29 CFR

**Features:** 2-1222 features a 2 plies of interwoven fabric bonded together to create a tough, flat running conveyor belt. PC2 B225 CBS is popular where a stable, cross rigid belt is required. It is an excellent light duty bucket elevator belt.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39