



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 2-1352: B3500 CBS

**Color:** Black

**Plies:** 1

**Nom. OAG:** 0.31" +/- 0.03"

**Fabric:** Interwoven Polyester

**Top Surface:** Smooth Cover

**Bottom Surface:** Smooth Cover

**Compound:** PVC

**Work Tension:** 350 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.165 lbs./PIW

**Minimum Pulley:** 8"

**Backflex Min. Pulley Dia.:** 12"

**Working Temp. (F):** 0 to 180

**Max. Stocked Width:** 48"

**Attributes:** Static Conductive to  $< 3 \times 10^8$  ohms, OSHA 29 CFR, Fire Retardant

**Features:** 2-1352 features an fire retardant, static conductive, oil resistant PVC. The tightly woven carcass resists fraying, has low stretch and has good lace retention. Do not use this belt on a slider bed application. B3500 CBS is a popular heavy duty bucket elevator belt and a heavy duty live roller belt. The thick carcass has good bolt retention. It is static conductive to less than 300 megohms per the OSHA requirement for bucket elevator conveyor belts.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39