



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

2-1421: RAV3 T140 COS

Color: Tan

Plies: 3

Nom. OAG: 0.135" +/- 0.02"

Fabric: Polyester

Top Surface: Smooth (Dull Finish)

Bottom Surface: Friction Surface

Compound: RAV

Work Tension: 150 lbs./PIW

Elongation: Less than 2%

Weight: 0.08 lbs./PIW

Minimum Pulley: 3"

Backflex Min. Pulley Dia.: 4.5"

Working Temp. (F): 20 to 180

Max. Stocked Width: 72"

Attributes: FDA Compliant, Oil Resistant,
Sliderbed Suitable

Features: 2-1421 features the popular RAV compound on a low stretch, stable polyester carcass. The RAV compound blends the economical benefits of PVC and the universal benefits of NBR. RAV3 T140 COS can be used almost anywhere a light duty food belt is needed. It is oil, grease and moisture resistant. The thermoplastic component lends itself to all types of fabrication. This belt is popular in chicken processing plants due to its stain resistance.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39