



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

2-1452: B4500 CBS

Color: Black

Plies: 1

Nom. OAG: 0.34" +/- 0.03"

Fabric: Interwoven Polyester

Top Surface: Smooth Cover

Bottom Surface: Smooth Cover

Compound: PVC

Work Tension: 450 lbs./PIW

Elongation: Less than 2%

Weight: 0.185 lbs./PIW

Minimum Pulley: 10"

Backflex Min. Pulley Dia.: 15"

Working Temp. (F): 0 to 180

Max. Stocked Width: 48"

Attributes: Static Conductive to $< 3 \times 10^8$ ohms, OSHA 29 CFR, Fire Retardant

Features: 2-1452 features fire retardant, static conductive, oil resistant PVC covers on both sides. The tightly woven fabric resists fraying, is stretch resistant and has good bolt retention. B4500 CBS is popular as a heavy duty bucket elevator belt or as a heavy live roller belt. Do not use this product in a slider bed application. It is static conductive to less than 300 megohms per the OSHA requirement for bucket elevator conveyor belts.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39