



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

3-1102: 2 Ply Black R/T

Color: Black

Plies: 2

Nom. OAG: 0.25" +/- 0.02"

Recessed OAG: 0.11"

Fabric: Polyester

Top Surface: Rubber Hemp Impression

Bottom Surface: Bare

Compound: SBR

Work Tension: 150 lbs./PIW

Elongation: Less than 2%

Weight: 0.11 lbs./PIW

Minimum Pulley: 2"

Backflex Min. Pulley Dia.: 3"

Working Temp. (F): -20 to 250

Max. Stocked Width: 72"

Attributes: Troughable, Sliderbed
Suitable

Top Cover Coefficient of Friction: 1.6

Bottom Cover Coefficient of Friction:
0.4

Features: This belt offers excellent gripping for standard incline conveyors. The polyester carcass offers high strength and low stretch. NOTE--The rough top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 2 Ply Black rough top is the most popular incline belt in our product line. It will handle almost all products including boxed, bagged or packaged goods.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39