



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

3-1103: 3 Ply Rubber R/T

Color: Black

Plies: 3

Nom. OAG: 0.3" +/- 0.02"

Recessed OAG: 0.15"

Fabric: Cotton/Polyester

Top Surface: Rubber Hemp Impression

Bottom Surface: Friction Surface

Compound: SBR

Work Tension: 100 lbs./PIW

Elongation: Less than 2%

Weight: 0.12 lbs./PIW

Minimum Pulley: 2.5"

Backflex Min. Pulley Dia.: 3.75"

Working Temp. (F): -20 to 250

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable,
Troughable

Top Cover Coefficient of Friction: 1

Bottom Cover Coefficient of Friction:
0.4

Features: This belt offers excellent gripping for standard incline conveyors. The Cotton/Polyester carcass gives a hefty appearance and a cushioning effect on the conveyed product. NOTE--The Rough Top must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 3 Ply Rubber R/T will handle most all products including boxed, bagged or packaged goods. This is also very popular as pulley lagging.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39