



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 3-1203: 3 Ply Neoprene R/T

**Color:** Brown

**Plies:** 3

**Nom. OAG:** 0.255" +/- 0.02"

**Recessed OAG:** 0.11"

**Fabric:** Polyester

**Top Surface:** Hemp Impression Rough  
Top

**Bottom Surface:** Bare

**Compound:** NBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.11 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** Troughable, Sliderbed  
Suitable

**Top Cover Coefficient of Friction:** 0.7

**Bottom Cover Coefficient of Friction:**  
0.3

**Features:** 3-1203 offers excellent gripping for standard incline conveyors. The NBR compound is oil resistant and non-marking. NOTE--The Rough Top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 3 Ply Neoprene Rough Top is popular in any area where a non-marking oil resistant rough top is needed. It is popular in the corrugated box industry as well as bakeries.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39