



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 3-1213: 3 Ply MOR Rough Top

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.3" +/- 0.03"

**Recessed OAG:** 0.13"

**Fabric:** Cotton/Polyester

**Top Surface:** Hemp Impression Rough  
Top

**Bottom Surface:** Bare Surface

**Compound:** MOR

**Work Tension:** 225 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.12 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp. (F):** -20 to 250

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable,  
Troughable, Oil Resistant

**Top Cover Coefficient of Friction:** 1

**Bottom Cover Coefficient of Friction:**  
0.3

**Features:** 3-1213 offers excellent gripping for standard incline conveyors. The MOR compound ensures oil resistant. The Cotton/Polyester carcass gives a hefty appearance and a cushioning effect on the conveyed product. NOTE--The Rough Top must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 3 Ply MOR Rough Top will handle most all products including boxed, bagged or packaged goods. The MOR is oil resistant.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39