



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

3-1303: 3 Ply Orange R/T

Color: Orange

Plies: 3

Nom. OAG: 0.245" +/- 0.02"

Recessed OAG: 0.13"

Fabric: Polyester

Top Surface: Hemp Impression Rough
Top

Bottom Surface: Skim

Compound: XNBR

Work Tension: 135 lbs./PIW

Elongation: Less than 2%

Weight: 0.11 lbs./PIW

Minimum Pulley: 2"

Backflex Min. Pulley Dia.: 3"

Working Temp. (F): 0 to 250

Max. Stocked Width: 72"

Attributes: Abrasion Resistant

Features: The Carboxylated NBR compound has enhanced wear resistance and oil resistance. NOTE--The Rough Top must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 3 Ply Orange R/T is particularly popular in the paper and cardboard box industry. It is also popular in any application where high abrasion or oily conditions exist.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39