



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 3-1406: 3 Ply Tan Rough Top x Bare

**Color:** Tan

**Plies:** 3

**Nom. OAG:** 0.265" +/- 0.025"

**Recessed OAG:** 0.12"

**Fabric:** Polyester

**Top Surface:** Hemp Impression Rough  
Top

**Bottom Surface:** Bare

**Compound:** SBR

**Work Tension:** 200 lbs./PIW

**Weight:** 0.1 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp. (F):** -20 to 250

**Max. Stocked Width:** 72"

**Attributes:** Non-Marking, Troughable,  
Sliderbed Suitable

**Top Cover Coefficient of Friction:** 1.2

**Bottom Cover Coefficient of Friction:**  
0.3

**Features:** 3-1406 offers one of the highest coefficients of friction for steep inclines. This belt cushions the conveyed product with a non-marking surface. NOTE--The Rough Top impression must be recessed to use the recommended lacing. Use Recessed OAG for Lacing Recommendation. 3 Ply Tan Rough Top X Bare is popular where a little extra grip or non-marking quality is needed in an incline belt.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39