



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

3-1407: 4 Ply Tan Gum R/T

Color: Tan

Plies: 4

Nom. OAG: 0.35" +/- 0.02"

Recessed OAG: 0.175"

Fabric: Polyester

Top Surface: Hemp Impression Rough
Top

Bottom Surface: Bare

Compound: NR

Work Tension: 200 lbs./PIW

Elongation: Less than 2%

Weight: 0.13 lbs./PIW

Minimum Pulley: 4"

Backflex Min. Pulley Dia.: 6"

Working Temp. (F): -40 to 250

Max. Stocked Width: 72"

Attributes: Non-Marking, Troughable,
Sliderbed Suitable

Top Cover Coefficient of Friction: 1.4

Bottom Cover Coefficient of Friction:
0.22

Features: 3-1407 offers one of the highest co-efficients of friction for steep inclines. This belt cushions the conveyed product with a non-marking surface. NOTE--The rough top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 4 Ply Tan Rough Top X Bare is popular where a little extra grip or non-marking quality is needed in an incline belt.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39