



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

3-1502: P2G Mono-Ruff-H 8M/HP/BP

Color: Green

Plies: 2

Nom. OAG: 0.265" +/- 0.02"

Recessed OAG: 0.08"

Fabric: Monofilament

Top Surface: Hemp Impression Rough
Top

Bottom Surface: Bare

Compound: PVC

Work Tension: 100 lbs./PIW

Elongation: Less than 2%

Weight: 0.071 lbs./PIW

Minimum Pulley: 3"

Backflex Min. Pulley Dia.: 4.5"

Working Temp. (F): 20 to 180

Max. Stocked Width: 72"

Attributes: Cross Rigid, Anti-Static,
Sliderbed Suitable

Features: 3-1502 features a PVC compound with a Hemp Impression Top Cover. It offers excellent gripping for standard incline conveyors. The carcass is high strength and low stretch. This belt is anti-static. NOTE--The rough top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. P2G Mono-Ruff-H 8M/HP/BP will handle most all products including boxed, bagged or packaged goods. This belt is non-marking belt. It will lie flat due to the monofilament carcass.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39