



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 3-1514: P2G Rough Top - Sine

**Color:** Green

**Plies:** 2

**Nom. OAG:** 0.22" +/- 0.01"

**Recessed OAG:** 0.16"

**Fabric:** Monofilament/Polyester

**Top Surface:** Sine Wave Rough Top  
Impression

**Bottom Surface:** Bare Surface

**Compound:** PVC

**Work Tension:** 51 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.08 lbs./PIW

**Minimum Pulley:** 2.4"

**Backflex Min. Pulley Dia.:** 3.6"

**Working Temp. (F):** -14 to 158

**Max. Stocked Width:** 118.11"

**Attributes:** Sliderbed Suitable, Cross  
Rigid

**Features:** 3-1514 offers an abrasion resistant rough top impression for conveying on inclines. This belt is anti-static. NOTE-The rough top impression must be recessed before lacing. 3-1514 has a distinctive rough top pattern in a sine wave configuration which is difficult to mistake. It is used in distribution centers, farming, furniture manufacturing, package handling, plastic manufacturing, synthetics/rubber and the wood industry.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39