



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

3-1517: R1700 PVC Rough Top-HI

Color: Red

Plies: 1

Nom. OAG: 0.34" +/- 0.01"

Recessed OAG: 0.165"

Fabric: Interwoven Polyester

Top Surface: Rough Top Impression

Bottom Surface: Brushed

Compound: PVC

Work Tension: 170 lbs./PIW

Elongation: Less than 2%

Weight: 0.117 lbs./PIW

Minimum Pulley: 4"

Backflex Min. Pulley Dia.: 6"

Working Temp. (F): 0 to 180

Max. Stocked Width: 72"

Top Cover Coefficient of Friction: 1.3

Bottom Cover Coefficient of Friction:
0.3

Features: 3-1517 features the popular interwoven carcass with a conventional hemp impression rough top. The belt has a brushed bottom surface for a low coefficient of friction. This belt also has some oil resistant qualities. NOTE--The impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. R1700 PVC R/T-HI Red can be used as a heavy duty incline belt where the angle is moderate. It is used to convey luggage, boxes, plastic, paper, corrugated cardboard, wood and lumber.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39