



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

3-2103: 3 Ply Black V-Top

Color: Black

Plies: 3

Nom. OAG: 0.322" +/- 0.02"

Recessed OAG: 0.14"

Fabric: Cotton/Polyester

Top Surface: V-Top pattern

Bottom Surface: Skim

Compound: SBR

Work Tension: 90 lbs./PIW

Elongation: Less than 2%

Weight: 0.135 lbs./PIW

Minimum Pulley: 2.5"

Backflex Min. Pulley Dia.: 3.75"

Working Temp. (F): -25 to 250

Max. Stocked Width: 60"

Top Cover Coefficient of Friction: 1

Bottom Cover Coefficient of Friction:
0.3

Features: This belt offers high incline capability for general purpose products. The belt is designed to self cleaning as it goes around the end pulleys. NOTE: The rough top profile must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 3 Ply Black V-Top is used primarily for general purpose inclines where the standard hemp impression rough top will not work. It is very popular in bottling and box handling.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39