



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

3-4402G: 2 Ply Tan Gum Diamond Top

Color: Tan

Plies: 2

Nom. OAG: 0.313" +/- 0.02"

Recessed OAG: 0.15"

Fabric: Polyester

Top Surface: Diamond Top Impression

Bottom Surface: Bare

Compound: SBR

Work Tension: 150 lbs./PIW

Elongation: Less than 2%

Weight: 0.103 lbs./PIW

Minimum Pulley: 2.5"

Working Temp. (F): -25 to 250

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable, Non-Marking

Top Cover Coefficient of Friction: 1.9

Bottom Cover Coefficient of Friction: 0.3

Features: 3-4402G is normally used for the most demanding steep inclines where high performance is needed. This belt has an unusually high coefficient of friction due to the gum rubber. NOTE--the rough top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 2 Ply Tan Gum Diamond Top is used for boxed, bagged and packaged goods applications. This belt is also popular in the airline industry and in the post office. This belt is also non-marking.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39