



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 3-4403: 3 Ply Tan Diamond Top

**Color:** Tan

**Plies:** 3

**Nom. OAG:** 0.365" +/- 0.02"

**Recessed OAG:** 0.185"

**Fabric:** Polyester

**Top Surface:** Diamond Top Impression

**Bottom Surface:** Bare

**Compound:** SBR

**Work Tension:** 225 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.128 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp. (F):** -25 to 250

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable

**Hardness:** 45a

**Top Cover Coefficient of Friction:** 1.9

**Bottom Cover Coefficient of Friction:**  
0.3

**Features:** 3-4403 is used for the steepest of inclines where high performance is needed/ The belt offers an unusually high coefficient of friction. NOTE--The rough top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 3 Ply Tan Diamond Top is used for boxed, bagged or packaged goods applications. The belt is also popular in the airline industry and post office. This belt is non-marking.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39