



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 3-5510: G1000 PVC Rough Top

**Color:** Green

**Plies:** 1

**Nom. OAG:** 0.24" +/- 0.02"

**Recessed OAG:** 0.11"

**Fabric:** Polyester

**Top Surface:** Hemp Impression Rough  
Top

**Bottom Surface:** Friction Surface

**Compound:** PVC

**Work Tension:** 100 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.078 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp. (F):** -10 to 180

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable

**Features:** 3-5510 features the popular interwoven carcass with a conventional hemp impression rough top. NOTE--Rough Top impression must be recessed to lace belt. Use Recessed OAG for Lacing Recommendation. G1000 PVC Rough Top can be used as a general purpose incline belt where the incline angle is moderate.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39