



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

4-1003: 3 Ply HS & W

Color: White

Plies: 3

Nom. OAG: 0.137" +/- 0.015"

Fabric: Cotton/Polyester

Top Surface: Bare

Bottom Surface: Friction Surface

Compound: SBR

Work Tension: 90 lbs./PIW

Elongation: Less than 2%

Weight: 0.061 lbs./PIW

Minimum Pulley: 2.5"

Backflex Min. Pulley Dia.: 3.75"

Working Temp. (F): -40 to 250

Max. Stocked Width: 720"

Top Cover Coefficient of Friction: 0.25

Bottom Cover Coefficient of Friction:
0.4

Features: 4-1003 features 3 cotton/polyester plies. Top cover up the belt offers a clean surface for conveying or accumulating. Top cover down it offers a low coefficient bottom cover. 3 Ply HS & W (Hot Stock and Water) is primarily used in the rubber and plastic industry to convey "Hot Stock." This belt is also popular in the airline industry.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39