



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

4-1004: 4 Ply HS & W

Color: White

Plies: 4

Nom. OAG: 0.18" +/- 0.02"

Fabric: Cotton/Polyester

Top Surface: Bare

Bottom Surface: Friction Surface

Compound: SBR

Work Tension: 100 lbs./PIW

Elongation: Less than 2%

Weight: 0.095 lbs./PIW

Minimum Pulley: 3"

Backflex Min. Pulley Dia.: 4.5"

Working Temp. (F): -20 to 250

Max. Stocked Width: 720"

Top Cover Coefficient of Friction: 0.25

Bottom Cover Coefficient of Friction:
0.4

Features: 4-1004 features 4 cotton/polyester plies. Top cover up this belt offers a clean surface for conveying or accumulating. Top cover down it offers a low coefficient bottom cover. 4 Ply HS & W (Hot Stock and Water) is primarily used in the rubber and plastic industry to convey "Hot Stock." This belt is also popular in the airline industry.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39