



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

4-1008: 2 Ply PVC x Bare CL8 A/S

Color: Green

Plies: 2

Nom. OAG: 0.08" +/- 0.01"

Fabric: Polyester

Top Surface: Smooth Cover

Bottom Surface: Bare Surface

Compound: PVC

Work Tension: 57 lbs./PIW

Elongation: Less than 2%

Weight: 0.04 lbs./PIW

Minimum Pulley: 1.3"

Backflex Min. Pulley Dia.: 2"

Working Temp. (F): 14 to 158

Max. Stocked Width: 78.75"

Attributes: Sliderbed Suitable, Cross Rigid, Anti-Static

Hardness: 80a

Features: 4-1008 is a general conveying belt. It is suitable for use on a slider bed or carrying rollers. It is used in distribution centers, packaging, furniture manufacturing, plastics manufacturing and in the wood industry. This belt is a general conveying belt in applications such as an infeed belt, discharge belt, line belt and an inspection/control belt.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39