



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

4-1012: 2 Ply PVC X Bare CL12 A/S

Color: Green

Plies: 2

Nom. OAG: 0.11" +/- 0.01"

Fabric: Polyester

Top Surface: Smooth Cover

Bottom Surface: Bare Surface

Compound: PVC

Work Tension: 74 lbs./PIW

Elongation: Less than 2%

Weight: 0.055 lbs./PIW

Minimum Pulley: 2"

Backflex Min. Pulley Dia.: 3"

Working Temp. (F): 14 to 158

Max. Stocked Width: 118.11"

Attributes: Anti-Static, Cross Rigid,
Sliderbed Suitable

Hardness: 80a

Features: 4-1012 is a general conveying belt. It is suitable for use on a slider bed or carrying rollers. It is used in distribution centers, packaging, furniture manufacturing, plastics manufacturing and in the wood industry. 4-1012 is available in a flame retardant compound conforming to ISO 340. This belt is a general conveying belt in applications such as an infeed belt, discharge belt, line belt and an inspection/control belt.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39