



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

4-1314Z: Blue Smooth Top Zip-Link x Bare

Color: Blue

Plies: 1

Nom. OAG: 0.134" +/- 0.015"

Fabric: Plastic Mesh

Top Surface: 1/32" Top Cover

Bottom Surface: Bare

Compound: XNBR

Work Tension: 150 lbs./PIW

Elongation: Less than 1%

Weight: 0.06 lbs./PIW

Minimum Pulley: 2"

Backflex Min. Pulley Dia.: 3.5"

Working Temp. (F): 0 to 250

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable

Top Cover Coefficient of Friction: 0.8

Bottom Cover Coefficient of Friction:
0.35

Features: The ziplink splice on this belt solves problems in applications where lace retention is a problem. The Carboxylated NBR carcass is extremely abrasion resistant. Blue Smooth Top Ziplink is a problem solving belt for light to medium industrial applications. The Ziplink splice combines the convenience of a laced belt with the splice tension rating of an endless belt and a smooth non-metallic splice. This belt is popular in canning operations and cardboard box plants.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39