



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

4-1500: 3 Ply Red Supergrip x FS

Color: Red

Plies: 3

Nom. OAG: 0.3" +/- 0.02"

Recessed OAG: 0.188"

Fabric: Polyester

Top Surface: 1/8" Natural Rubber Cover

Bottom Surface: Bare

Compound: NR

Work Tension: 200 lbs./PIW

Elongation: Less than 2%

Weight: 0.148 lbs./PIW

Minimum Pulley: 6"

Backflex Min. Pulley Dia.: 9"

Working Temp. (F): -20 to 250

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable

Top Cover Coefficient of Friction: 2.5

Bottom Cover Coefficient of Friction:
0.2

Features: This belt has a soft, highly abrasive rubber cover that has one of the highest coefficients of friction known. The rubber is molded to the belt in an uncured state (not glued) to insure a permanent bond. Red Supergrip x FS is primarily used in the corrugator box manufacture industry on folder gluer machines. It can also be used on other applications that require a pulling effect or on applications requiring a high coefficient of friction.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39