



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 4-1500Z: Red Supergrip Zip-Link

**Color:** Red

**Plies:** 1

**Nom. OAG:** 0.202" +/- 0.02"

**Fabric:** Plastic Mesh

**Top Surface:** 1/8" Smooth High Grip

**Bottom Surface:** Bare

**Compound:** NR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.1 lbs./PIW

**Minimum Pulley:** 4"

**Backflex Min. Pulley Dia.:** 6"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable

**Top Cover Coefficient of Friction:** 2.5

**Bottom Cover Coefficient of Friction:**  
0.4

**Features:** 4-1500Z features a 1/8" top surface that is very tacky. The cover is abrasion resistant and offers a high coefficient of friction. The belt can be put together by a pin from its own carcass. Red Supergrip Ziplink is used in corrugator box plants, sanding machines and any other light or medium industrial application. The Ziplink splice is smooth and non-metallic and combines the convenience of a laced belt with the splice tension rating of an endless belt.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39