



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 4-2003: 3 Ply Black OHGR

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.135" +/- 0.03"

**Fabric:** Polyester

**Top Surface:** Smooth

**Bottom Surface:** Friction

**Compound:** NBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.065 lbs./PIW

**Minimum Pulley:** 4"

**Backflex Min. Pulley Dia.:** 6"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable

**Top Cover Coefficient of Friction:** 1.8

**Bottom Cover Coefficient of Friction:**  
0.6

**Features:** This belt features a oil, heat and grease resistant compound. 3 Ply Black OHGR is a popular general conveying belt. It features oil, heat and grease resistance and is commonly used in agricultural and oily applications where PVC does not perform well.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39