



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 4-3003L: 3 Ply Tan Transmission LD

**Color:** Tan

**Plies:** 3

**Nom. OAG:** 0.127" +/- 0.01"

**Fabric:** Cotton

**Top Surface:** Friction Surface

**Bottom Surface:** Friction Surface

**Compound:** SBR

**Work Tension:** 90 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.056 lbs./PIW

**Minimum Pulley:** 2.5"

**Backflex Min. Pulley Dia.:** 3.75"

**Working Temp. (F):** -40 to 250

**Max. Stocked Width:** 72"

**Top Cover Coefficient of Friction:** 0.6

**Bottom Cover Coefficient of Friction:**  
0.6

**Features:** 4-3003L 3 plies of heavy duty cotton together with heavy skims between plies. The tan rubber insures a non-marking belt. 3 Ply Tan Transmission LD is an old time favorite for the feed and grain industry for general purpose conveyors and light duty bucket elevators. The belt is also used in power transmission applications.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39