



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 4-3008: 5 Ply Tan Transmission LD

**Color:** Tan

**Plies:** 5

**Nom. OAG:** 0.225" +/- 0.03"

**Fabric:** Cotton/Polyester

**Top Surface:** Friction Surface

**Bottom Surface:** Friction Surface

**Compound:** SBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.101 lbs./PIW

**Minimum Pulley:** 3.5"

**Backflex Min. Pulley Dia.:** 5.25"

**Working Temp. (F):** -40 to 250

**Max. Stocked Width:** 72"

**Top Cover Coefficient of Friction:** 0.6

**Bottom Cover Coefficient of Friction:**  
0.6

**Features:** 4-3008 features 5 plies of cotton bonded together with heavy SBR skims. The tan rubber ensures a non-marking belt. 5 Ply Tan Transmission LD is an old time favorite in the feed and grain industry for general purpose conveying and light duty elevators. The belt is also used in heavy power transmission.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39