



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 4-4002: 150 1/32 X Bare

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.125" +/- 0.02"

**Fabric:** Polyester

**Top Surface:** 1/32" SBR Cover

**Top Cover Thickness:** 0.0312"

**Bottom Surface:** Bare

**Compound:** SBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.08 lbs./PIW

**Minimum Pulley:** 4"

**Backflex Min. Pulley Dia.:** 6"

**Working Temp. (F):** -20 to 250

**Max. Stocked Width:** 84"

**Attributes:** Sliderbed Suitable,  
Troughable

**Features:** 4-4002 features an abrasion resistant cover. The belt can be used as a light duty general purpose belt. 150 1/32" x Bare is popular in many agricultural applications. It also used in the airline industry and for conveying packaged good. It is a very good belt to use for rubber fabrication.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39