



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 4-4004: 4 Ply Slider Top

**Color:** Tan

**Plies:** 4

**Nom. OAG:** 0.12" +/- 0.02"

**Fabric:** Cotton/Polyester

**Top Surface:** Bare Nylon

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 50 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.069 lbs./PIW

**Minimum Pulley:** 2"

**Backflex Min. Pulley Dia.:** 3"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Top Cover Coefficient of Friction:** 0.3

**Bottom Cover Coefficient of Friction:**  
0.5

**Features:** This belt offers a hard abrasion resistant nylon top surface that is almost frictionless. The belt was designed for automated machinery where the product must accumulate or stay stationary as the belt moves. 4 Ply Slider Top is used in many packaging and diverting operations where the product must slide on the belt while the belt is moving.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39