



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

4-4680: R900 Red Urethane

Color: Red

Plies: 1

Nom. OAG: 0.125" +/- 0.02"

Fabric: Interwoven Polyester

Top Surface: Smooth Cover

Bottom Surface: Friction Surface

Compound: Poly Urethane

Work Tension: 90 lbs./PIW

Elongation: Less than 2%

Weight: 0.079 lbs./PIW

Minimum Pulley: 2"

Backflex Min. Pulley Dia.: 3"

Working Temp. (F): 0 to 185

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable, Abrasion Resistant

Hardness: 85a

Top Cover Coefficient of Friction: 0.85

Bottom Cover Coefficient of Friction: 0.25

Features: This is one of the toughest, most abrasive resistant belts available. The 85 Durometer urethane cover will resist cutting and abrasion from metal, glass, aluminum and other abrasive materials. R900 Red Urethane is used in Metal Stamping, Recycling, Die Cutting and Brick Manufacturing applications.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39